

CABLE DESIGN SHEET																																																																																																																																							
CABLE DESCRIPTION: Cat. 6A F/FTP 4x2xAWG23/1 (LSZH-FR Sheath for Indoor Installation)																																																																																																																																							
FIRE CLASS: Not Required			CABLE CODE: LAN645ZH-FR (Rev.0)																																																																																																																																				
<table style="width: 100%; border-collapse: collapse;"> <tr> <td></td> <td style="text-align: center;">(Cu)</td> <td style="text-align: center;">(PEG)</td> <td style="text-align: center;">(Al/Pet)</td> <td style="text-align: center;">(Al/Pet)</td> <td style="text-align: center;">(LSZH-FR)</td> </tr> <tr> <td style="text-align: center;">Ø (mm)</td> <td style="text-align: center;">0,57</td> <td style="text-align: center;">1,35</td> <td style="text-align: center;">PIMF</td> <td></td> <td style="text-align: center;">8,30</td> </tr> </table>						(Cu)	(PEG)	(Al/Pet)	(Al/Pet)	(LSZH-FR)	Ø (mm)	0,57	1,35	PIMF		8,30																																																																																																																							
	(Cu)	(PEG)	(Al/Pet)	(Al/Pet)	(LSZH-FR)																																																																																																																																		
Ø (mm)	0,57	1,35	PIMF		8,30																																																																																																																																		
<table style="width: 100%; border-collapse: collapse;"> <tr> <th style="text-align: left; width: 50%;"><u>CONSTRUCTION DATA:</u></th> <th style="text-align: left; width: 50%;"><u>DIMENSIONS:</u></th> </tr> <tr> <td style="vertical-align: top;"> A. 4 pairs of bare copper wires B. Skin/foam/skin Polyethylene insulation Colour code: pair 1: white - blue pair 2: white - orange pair 3: white - green pair 4: white - brown C. Overall Al/Pet foil shielded pairs, PiMF mode D. Drain wire of tinned copper E. Aluminium/Polyester reversed tape spirally wound F. Orange Outer sheath of halogen-free, low smoke, flame retardant and UV-resistant material. printed by inkjet: CAVEL LAN 645 ZH-FR MADE IN ITALY CAT 6A F/FTP 4x2xAWG23/1 ISO-IEC 11801 EN50173-1 CEI-UNEL 36762 C-4 (U0 =400V) gggaan meter marking (gggaan=batch) <table style="width: 100%; border-collapse: collapse; margin-top: 10px;"> <tr> <td style="width: 30%;">Weight of copper conductors (approx):</td> <td style="width: 10%;">19,8</td> <td style="width: 10%;">Kg/Km</td> <td style="width: 50%;">Temperature rating: -25°C/+70°C</td> </tr> <tr> <td>Total weight of cable (approx.) :</td> <td>70,3</td> <td>Kg/Km</td> <td>Max. Tensile Strength: 100 N</td> </tr> <tr> <td>Bending radius (operation/installation):</td> <td>70/35</td> <td>mm</td> <td></td> </tr> </table> </td> <td style="vertical-align: top;"> <table style="width: 100%; border-collapse: collapse; margin-top: 10px;"> <tr> <td style="width: 30%;">(Cu)</td> <td style="width: 10%;">φ</td> <td style="width: 10%;">0,57</td> <td style="width: 50%;">mm</td> </tr> <tr> <td>(PEG)</td> <td>φ</td> <td>1,35</td> <td>mm</td> </tr> <tr> <td>(Al/Pet)</td> <td></td> <td>14 x 40/23</td> <td>mm x μm</td> </tr> <tr> <td>(CuSn)</td> <td>φ</td> <td>0,40</td> <td>mm</td> </tr> <tr> <td>(Al/Pet)</td> <td></td> <td>27 x 30/19</td> <td>mm</td> </tr> <tr> <td>(LSZH-FR)</td> <td></td> <td>8,30</td> <td>mm</td> </tr> </table> </td> </tr> <tr> <td colspan="5" style="padding: 10px;"> <table style="width: 100%; border-collapse: collapse;"> <tr> <th style="text-align: left; width: 50%;"><u>ELECTRICAL DATA:</u></th> <th style="text-align: left; width: 50%;"></th> </tr> <tr> <td style="vertical-align: top;"> Characteristic Impedance (100 MHz): 100 ± 5 Ohm Mutual capacitance (800 Hz) : 43 pF/m Velocity ratio : 77 % Coupling Attenuation: > 45 dB Screening Attenuation (SA) : 30 -- 100 MHz > 70 dB ; 100 -- 500 MHz > 60 dB Transfer Impedance (Zt) : 1 MHz < 11 mOhm/m ; 10 MHz < 5 mOhm/m ; 30 MHz < 3 mOhm/m </td> <td style="vertical-align: top;"> Insulation resistance: > 5000 MΩ x km Conductor resistance: 73 Ohm/km Loop resistance: 146 Ohm/km Sheath Insulation voltage (DC 1 min): 1 kV </td> </tr> </table> </td> </tr> <tr> <td colspan="5" style="padding: 10px;"> <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th>Frequency (MHz)</th> <th>Attenuation (dB/100m)</th> <th>NEXT (dB)</th> <th>ACR-N (dB/100m)</th> <th>SRL (dB)</th> </tr> </thead> <tbody> <tr><td>1</td><td>2,1</td><td>90</td><td>87,9</td><td>25</td></tr> <tr><td>4</td><td>3,6</td><td>90</td><td>86,4</td><td>25</td></tr> <tr><td>10</td><td>5,4</td><td>90</td><td>84,6</td><td>25</td></tr> <tr><td>16</td><td>6,8</td><td>90</td><td>83,2</td><td>25</td></tr> <tr><td>20</td><td>7,7</td><td>85</td><td>77,3</td><td>25</td></tr> <tr><td>31,25</td><td>9,6</td><td>85</td><td>75,4</td><td>25</td></tr> <tr><td>62,5</td><td>13,7</td><td>80</td><td>66,3</td><td>25</td></tr> <tr><td>100</td><td>17,4</td><td>80</td><td>62,6</td><td>25</td></tr> <tr><td>155,5</td><td>21,9</td><td>80</td><td>58,1</td><td>25</td></tr> <tr><td>250</td><td>28,1</td><td>75</td><td>46,9</td><td>25</td></tr> <tr><td>450</td><td>38,3</td><td>70</td><td>31,7</td><td>25</td></tr> <tr><td>500</td><td>40,0</td><td>70</td><td>30,0</td><td>25</td></tr> </tbody> </table> </td> </tr> <tr> <td colspan="5" style="padding: 10px;"> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; vertical-align: top;"> STANDARDS: ISO/IEC 11801 Class Ea ; EN50173 ; EN50288-10-1 ; CEI-UNEL 36762 ; EN50575 </td> <td style="width: 50%; vertical-align: top;"> APPLICATION: Primary (Campus), Secondary (Riser), Tertiary (Horizontal) IPTV; HbbTV 2.0.n IEEE 802.3: 10Base-T; 100Base-T; 1000Base-T; 10GBase-T IEEE 802.5: ISDN; TPDDI; ATM; CATV; Broadband Video; PoE/PoE+ </td> </tr> </table> </td> </tr> <tr> <td colspan="2" style="padding: 10px;"> ITALIANA CONDUTTORI s.r.l V.le Zanotti 90 - 27027 Gropello Cairoli (PV)- Italy Tel. 0382-815150 - Fax: 0382-814212 </td> <td colspan="2" style="padding: 10px;"> Date Jun. 06, 2025 </td> <td style="padding: 10px;"> Responsible P.Piccinini </td> </tr> </table>					<u>CONSTRUCTION DATA:</u>	<u>DIMENSIONS:</u>	A. 4 pairs of bare copper wires B. Skin/foam/skin Polyethylene insulation Colour code: pair 1: white - blue pair 2: white - orange pair 3: white - green pair 4: white - brown C. Overall Al/Pet foil shielded pairs, PiMF mode D. Drain wire of tinned copper E. Aluminium/Polyester reversed tape spirally wound F. Orange Outer sheath of halogen-free, low smoke, flame retardant and UV-resistant material. printed by inkjet: CAVEL LAN 645 ZH-FR MADE IN ITALY CAT 6A F/FTP 4x2xAWG23/1 ISO-IEC 11801 EN50173-1 CEI-UNEL 36762 C-4 (U0 =400V) gggaan meter marking (gggaan=batch) <table style="width: 100%; border-collapse: collapse; margin-top: 10px;"> <tr> <td style="width: 30%;">Weight of copper conductors (approx):</td> <td style="width: 10%;">19,8</td> <td style="width: 10%;">Kg/Km</td> <td style="width: 50%;">Temperature rating: -25°C/+70°C</td> </tr> <tr> <td>Total weight of cable (approx.) :</td> <td>70,3</td> <td>Kg/Km</td> <td>Max. Tensile Strength: 100 N</td> </tr> <tr> <td>Bending radius (operation/installation):</td> <td>70/35</td> <td>mm</td> <td></td> </tr> </table>	Weight of copper conductors (approx):	19,8	Kg/Km	Temperature rating: -25°C/+70°C	Total weight of cable (approx.) :	70,3	Kg/Km	Max. Tensile Strength: 100 N	Bending radius (operation/installation):	70/35	mm		<table style="width: 100%; border-collapse: collapse; margin-top: 10px;"> <tr> <td style="width: 30%;">(Cu)</td> <td style="width: 10%;">φ</td> <td style="width: 10%;">0,57</td> <td style="width: 50%;">mm</td> </tr> <tr> <td>(PEG)</td> <td>φ</td> <td>1,35</td> <td>mm</td> </tr> <tr> <td>(Al/Pet)</td> <td></td> <td>14 x 40/23</td> <td>mm x μm</td> </tr> <tr> <td>(CuSn)</td> <td>φ</td> <td>0,40</td> <td>mm</td> </tr> <tr> <td>(Al/Pet)</td> <td></td> <td>27 x 30/19</td> <td>mm</td> </tr> <tr> <td>(LSZH-FR)</td> <td></td> <td>8,30</td> <td>mm</td> </tr> </table>	(Cu)	φ	0,57	mm	(PEG)	φ	1,35	mm	(Al/Pet)		14 x 40/23	mm x μm	(CuSn)	φ	0,40	mm	(Al/Pet)		27 x 30/19	mm	(LSZH-FR)		8,30	mm	<table style="width: 100%; border-collapse: collapse;"> <tr> <th style="text-align: left; width: 50%;"><u>ELECTRICAL DATA:</u></th> <th style="text-align: left; width: 50%;"></th> </tr> <tr> <td style="vertical-align: top;"> Characteristic Impedance (100 MHz): 100 ± 5 Ohm Mutual capacitance (800 Hz) : 43 pF/m Velocity ratio : 77 % Coupling Attenuation: > 45 dB Screening Attenuation (SA) : 30 -- 100 MHz > 70 dB ; 100 -- 500 MHz > 60 dB Transfer Impedance (Zt) : 1 MHz < 11 mOhm/m ; 10 MHz < 5 mOhm/m ; 30 MHz < 3 mOhm/m </td> <td style="vertical-align: top;"> Insulation resistance: > 5000 MΩ x km Conductor resistance: 73 Ohm/km Loop resistance: 146 Ohm/km Sheath Insulation voltage (DC 1 min): 1 kV </td> </tr> </table>					<u>ELECTRICAL DATA:</u>		Characteristic Impedance (100 MHz): 100 ± 5 Ohm Mutual capacitance (800 Hz) : 43 pF/m Velocity ratio : 77 % Coupling Attenuation: > 45 dB Screening Attenuation (SA) : 30 -- 100 MHz > 70 dB ; 100 -- 500 MHz > 60 dB Transfer Impedance (Zt) : 1 MHz < 11 mOhm/m ; 10 MHz < 5 mOhm/m ; 30 MHz < 3 mOhm/m	Insulation resistance: > 5000 MΩ x km Conductor resistance: 73 Ohm/km Loop resistance: 146 Ohm/km Sheath Insulation voltage (DC 1 min): 1 kV	<table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th>Frequency (MHz)</th> <th>Attenuation (dB/100m)</th> <th>NEXT (dB)</th> <th>ACR-N (dB/100m)</th> <th>SRL (dB)</th> </tr> </thead> <tbody> <tr><td>1</td><td>2,1</td><td>90</td><td>87,9</td><td>25</td></tr> <tr><td>4</td><td>3,6</td><td>90</td><td>86,4</td><td>25</td></tr> <tr><td>10</td><td>5,4</td><td>90</td><td>84,6</td><td>25</td></tr> <tr><td>16</td><td>6,8</td><td>90</td><td>83,2</td><td>25</td></tr> <tr><td>20</td><td>7,7</td><td>85</td><td>77,3</td><td>25</td></tr> <tr><td>31,25</td><td>9,6</td><td>85</td><td>75,4</td><td>25</td></tr> <tr><td>62,5</td><td>13,7</td><td>80</td><td>66,3</td><td>25</td></tr> <tr><td>100</td><td>17,4</td><td>80</td><td>62,6</td><td>25</td></tr> <tr><td>155,5</td><td>21,9</td><td>80</td><td>58,1</td><td>25</td></tr> <tr><td>250</td><td>28,1</td><td>75</td><td>46,9</td><td>25</td></tr> <tr><td>450</td><td>38,3</td><td>70</td><td>31,7</td><td>25</td></tr> <tr><td>500</td><td>40,0</td><td>70</td><td>30,0</td><td>25</td></tr> </tbody> </table>					Frequency (MHz)	Attenuation (dB/100m)	NEXT (dB)	ACR-N (dB/100m)	SRL (dB)	1	2,1	90	87,9	25	4	3,6	90	86,4	25	10	5,4	90	84,6	25	16	6,8	90	83,2	25	20	7,7	85	77,3	25	31,25	9,6	85	75,4	25	62,5	13,7	80	66,3	25	100	17,4	80	62,6	25	155,5	21,9	80	58,1	25	250	28,1	75	46,9	25	450	38,3	70	31,7	25	500	40,0	70	30,0	25	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; vertical-align: top;"> STANDARDS: ISO/IEC 11801 Class Ea ; EN50173 ; EN50288-10-1 ; CEI-UNEL 36762 ; EN50575 </td> <td style="width: 50%; vertical-align: top;"> APPLICATION: Primary (Campus), Secondary (Riser), Tertiary (Horizontal) IPTV; HbbTV 2.0.n IEEE 802.3: 10Base-T; 100Base-T; 1000Base-T; 10GBase-T IEEE 802.5: ISDN; TPDDI; ATM; CATV; Broadband Video; PoE/PoE+ </td> </tr> </table>					STANDARDS: ISO/IEC 11801 Class Ea ; EN50173 ; EN50288-10-1 ; CEI-UNEL 36762 ; EN50575	APPLICATION: Primary (Campus), Secondary (Riser), Tertiary (Horizontal) IPTV; HbbTV 2.0.n IEEE 802.3: 10Base-T; 100Base-T; 1000Base-T; 10GBase-T IEEE 802.5: ISDN; TPDDI; ATM; CATV; Broadband Video; PoE/PoE+	ITALIANA CONDUTTORI s.r.l V.le Zanotti 90 - 27027 Gropello Cairoli (PV)- Italy Tel. 0382-815150 - Fax: 0382-814212		Date Jun. 06, 2025		Responsible P.Piccinini
<u>CONSTRUCTION DATA:</u>	<u>DIMENSIONS:</u>																																																																																																																																						
A. 4 pairs of bare copper wires B. Skin/foam/skin Polyethylene insulation Colour code: pair 1: white - blue pair 2: white - orange pair 3: white - green pair 4: white - brown C. Overall Al/Pet foil shielded pairs, PiMF mode D. Drain wire of tinned copper E. Aluminium/Polyester reversed tape spirally wound F. Orange Outer sheath of halogen-free, low smoke, flame retardant and UV-resistant material. printed by inkjet: CAVEL LAN 645 ZH-FR MADE IN ITALY CAT 6A F/FTP 4x2xAWG23/1 ISO-IEC 11801 EN50173-1 CEI-UNEL 36762 C-4 (U0 =400V) gggaan meter marking (gggaan=batch) <table style="width: 100%; border-collapse: collapse; margin-top: 10px;"> <tr> <td style="width: 30%;">Weight of copper conductors (approx):</td> <td style="width: 10%;">19,8</td> <td style="width: 10%;">Kg/Km</td> <td style="width: 50%;">Temperature rating: -25°C/+70°C</td> </tr> <tr> <td>Total weight of cable (approx.) :</td> <td>70,3</td> <td>Kg/Km</td> <td>Max. Tensile Strength: 100 N</td> </tr> <tr> <td>Bending radius (operation/installation):</td> <td>70/35</td> <td>mm</td> <td></td> </tr> </table>	Weight of copper conductors (approx):	19,8	Kg/Km	Temperature rating: -25°C/+70°C	Total weight of cable (approx.) :	70,3	Kg/Km	Max. Tensile Strength: 100 N	Bending radius (operation/installation):	70/35	mm		<table style="width: 100%; border-collapse: collapse; margin-top: 10px;"> <tr> <td style="width: 30%;">(Cu)</td> <td style="width: 10%;">φ</td> <td style="width: 10%;">0,57</td> <td style="width: 50%;">mm</td> </tr> <tr> <td>(PEG)</td> <td>φ</td> <td>1,35</td> <td>mm</td> </tr> <tr> <td>(Al/Pet)</td> <td></td> <td>14 x 40/23</td> <td>mm x μm</td> </tr> <tr> <td>(CuSn)</td> <td>φ</td> <td>0,40</td> <td>mm</td> </tr> <tr> <td>(Al/Pet)</td> <td></td> <td>27 x 30/19</td> <td>mm</td> </tr> <tr> <td>(LSZH-FR)</td> <td></td> <td>8,30</td> <td>mm</td> </tr> </table>	(Cu)	φ	0,57	mm	(PEG)	φ	1,35	mm	(Al/Pet)		14 x 40/23	mm x μm	(CuSn)	φ	0,40	mm	(Al/Pet)		27 x 30/19	mm	(LSZH-FR)		8,30	mm																																																																																																		
Weight of copper conductors (approx):	19,8	Kg/Km	Temperature rating: -25°C/+70°C																																																																																																																																				
Total weight of cable (approx.) :	70,3	Kg/Km	Max. Tensile Strength: 100 N																																																																																																																																				
Bending radius (operation/installation):	70/35	mm																																																																																																																																					
(Cu)	φ	0,57	mm																																																																																																																																				
(PEG)	φ	1,35	mm																																																																																																																																				
(Al/Pet)		14 x 40/23	mm x μm																																																																																																																																				
(CuSn)	φ	0,40	mm																																																																																																																																				
(Al/Pet)		27 x 30/19	mm																																																																																																																																				
(LSZH-FR)		8,30	mm																																																																																																																																				
<table style="width: 100%; border-collapse: collapse;"> <tr> <th style="text-align: left; width: 50%;"><u>ELECTRICAL DATA:</u></th> <th style="text-align: left; width: 50%;"></th> </tr> <tr> <td style="vertical-align: top;"> Characteristic Impedance (100 MHz): 100 ± 5 Ohm Mutual capacitance (800 Hz) : 43 pF/m Velocity ratio : 77 % Coupling Attenuation: > 45 dB Screening Attenuation (SA) : 30 -- 100 MHz > 70 dB ; 100 -- 500 MHz > 60 dB Transfer Impedance (Zt) : 1 MHz < 11 mOhm/m ; 10 MHz < 5 mOhm/m ; 30 MHz < 3 mOhm/m </td> <td style="vertical-align: top;"> Insulation resistance: > 5000 MΩ x km Conductor resistance: 73 Ohm/km Loop resistance: 146 Ohm/km Sheath Insulation voltage (DC 1 min): 1 kV </td> </tr> </table>					<u>ELECTRICAL DATA:</u>		Characteristic Impedance (100 MHz): 100 ± 5 Ohm Mutual capacitance (800 Hz) : 43 pF/m Velocity ratio : 77 % Coupling Attenuation: > 45 dB Screening Attenuation (SA) : 30 -- 100 MHz > 70 dB ; 100 -- 500 MHz > 60 dB Transfer Impedance (Zt) : 1 MHz < 11 mOhm/m ; 10 MHz < 5 mOhm/m ; 30 MHz < 3 mOhm/m	Insulation resistance: > 5000 MΩ x km Conductor resistance: 73 Ohm/km Loop resistance: 146 Ohm/km Sheath Insulation voltage (DC 1 min): 1 kV																																																																																																																															
<u>ELECTRICAL DATA:</u>																																																																																																																																							
Characteristic Impedance (100 MHz): 100 ± 5 Ohm Mutual capacitance (800 Hz) : 43 pF/m Velocity ratio : 77 % Coupling Attenuation: > 45 dB Screening Attenuation (SA) : 30 -- 100 MHz > 70 dB ; 100 -- 500 MHz > 60 dB Transfer Impedance (Zt) : 1 MHz < 11 mOhm/m ; 10 MHz < 5 mOhm/m ; 30 MHz < 3 mOhm/m	Insulation resistance: > 5000 MΩ x km Conductor resistance: 73 Ohm/km Loop resistance: 146 Ohm/km Sheath Insulation voltage (DC 1 min): 1 kV																																																																																																																																						
<table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th>Frequency (MHz)</th> <th>Attenuation (dB/100m)</th> <th>NEXT (dB)</th> <th>ACR-N (dB/100m)</th> <th>SRL (dB)</th> </tr> </thead> <tbody> <tr><td>1</td><td>2,1</td><td>90</td><td>87,9</td><td>25</td></tr> <tr><td>4</td><td>3,6</td><td>90</td><td>86,4</td><td>25</td></tr> <tr><td>10</td><td>5,4</td><td>90</td><td>84,6</td><td>25</td></tr> <tr><td>16</td><td>6,8</td><td>90</td><td>83,2</td><td>25</td></tr> <tr><td>20</td><td>7,7</td><td>85</td><td>77,3</td><td>25</td></tr> <tr><td>31,25</td><td>9,6</td><td>85</td><td>75,4</td><td>25</td></tr> <tr><td>62,5</td><td>13,7</td><td>80</td><td>66,3</td><td>25</td></tr> <tr><td>100</td><td>17,4</td><td>80</td><td>62,6</td><td>25</td></tr> <tr><td>155,5</td><td>21,9</td><td>80</td><td>58,1</td><td>25</td></tr> <tr><td>250</td><td>28,1</td><td>75</td><td>46,9</td><td>25</td></tr> <tr><td>450</td><td>38,3</td><td>70</td><td>31,7</td><td>25</td></tr> <tr><td>500</td><td>40,0</td><td>70</td><td>30,0</td><td>25</td></tr> </tbody> </table>					Frequency (MHz)	Attenuation (dB/100m)	NEXT (dB)	ACR-N (dB/100m)	SRL (dB)	1	2,1	90	87,9	25	4	3,6	90	86,4	25	10	5,4	90	84,6	25	16	6,8	90	83,2	25	20	7,7	85	77,3	25	31,25	9,6	85	75,4	25	62,5	13,7	80	66,3	25	100	17,4	80	62,6	25	155,5	21,9	80	58,1	25	250	28,1	75	46,9	25	450	38,3	70	31,7	25	500	40,0	70	30,0	25																																																																		
Frequency (MHz)	Attenuation (dB/100m)	NEXT (dB)	ACR-N (dB/100m)	SRL (dB)																																																																																																																																			
1	2,1	90	87,9	25																																																																																																																																			
4	3,6	90	86,4	25																																																																																																																																			
10	5,4	90	84,6	25																																																																																																																																			
16	6,8	90	83,2	25																																																																																																																																			
20	7,7	85	77,3	25																																																																																																																																			
31,25	9,6	85	75,4	25																																																																																																																																			
62,5	13,7	80	66,3	25																																																																																																																																			
100	17,4	80	62,6	25																																																																																																																																			
155,5	21,9	80	58,1	25																																																																																																																																			
250	28,1	75	46,9	25																																																																																																																																			
450	38,3	70	31,7	25																																																																																																																																			
500	40,0	70	30,0	25																																																																																																																																			
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; vertical-align: top;"> STANDARDS: ISO/IEC 11801 Class Ea ; EN50173 ; EN50288-10-1 ; CEI-UNEL 36762 ; EN50575 </td> <td style="width: 50%; vertical-align: top;"> APPLICATION: Primary (Campus), Secondary (Riser), Tertiary (Horizontal) IPTV; HbbTV 2.0.n IEEE 802.3: 10Base-T; 100Base-T; 1000Base-T; 10GBase-T IEEE 802.5: ISDN; TPDDI; ATM; CATV; Broadband Video; PoE/PoE+ </td> </tr> </table>					STANDARDS: ISO/IEC 11801 Class Ea ; EN50173 ; EN50288-10-1 ; CEI-UNEL 36762 ; EN50575	APPLICATION: Primary (Campus), Secondary (Riser), Tertiary (Horizontal) IPTV; HbbTV 2.0.n IEEE 802.3: 10Base-T; 100Base-T; 1000Base-T; 10GBase-T IEEE 802.5: ISDN; TPDDI; ATM; CATV; Broadband Video; PoE/PoE+																																																																																																																																	
STANDARDS: ISO/IEC 11801 Class Ea ; EN50173 ; EN50288-10-1 ; CEI-UNEL 36762 ; EN50575	APPLICATION: Primary (Campus), Secondary (Riser), Tertiary (Horizontal) IPTV; HbbTV 2.0.n IEEE 802.3: 10Base-T; 100Base-T; 1000Base-T; 10GBase-T IEEE 802.5: ISDN; TPDDI; ATM; CATV; Broadband Video; PoE/PoE+																																																																																																																																						
ITALIANA CONDUTTORI s.r.l V.le Zanotti 90 - 27027 Gropello Cairoli (PV)- Italy Tel. 0382-815150 - Fax: 0382-814212		Date Jun. 06, 2025		Responsible P.Piccinini																																																																																																																																			